

0362

ELECTRONIC CUTTING BAND SAW FOR BENCH

With inverter motor.



Blade dimensions	1435 x 12,7 x 0,65 mm
Motor	230 V 50 60 Hz 0,4 kW
Cutting speed	35 ÷ 80 m/min
Cut range	0° ÷ 60°
Cutting depth at 90°	• 125 mm ■ 125 mm
Cutting depth at 45°	• 76 mm ■ 76 mm
Dimensions	700 x 360 x 450h mm
Net weight	22 kg



0132

CUTTING BAND SAW

Bench type, easy to carry, with two cutting speed.



Blade dimensions	1335 x 12,7 x 0,65 mm
Speed	(2) 60 80 m / min
Cut range	0° ÷ 45°
Motor	230 V 50 Hz 0,850 kW
Cutting depth at 90°	• 105 mm — 105 x 93 mm
Cutting depth at 45°	• 72 mm — 70 x 60 mm
Net weight	17 kg



0522

FOLDING STAND

Sturdy and resistant frame, adjustable height.



Capacity	150 kg
Plate Dimensions	820 x 460 mm
Working height	600 - 715 - 745 - 770 - 795 - 820 mm
Rollers distance	870 - 1070 - 1350 mm
Rollers height	37 ÷ 470 mm
Net weight	17 kg

0133

ROLLER STAND



Roller shaft diameter	Ø 52 x 350 mm
Height	690 / 1200 mm
Maximum capacity	800 kg
Net weight	15 kg

R003/09
PANTOGRAPH ROLLER CONVEYOR


Capacity	130 kg
Roller diameter	50 mm
Length	485 ÷ 1400 mm
Height	610 ÷ 950 mm
Size	1460 x 660 x 950 h mm
Net weight	31 kg

R001-
ADJUSTABLE HEIGHT ROLLER STAND

With independent height adjustment feet.



Art.	Dimensions	Rollers distance	Roller dimensions	Height	Maximum capacity	Net weight
R001/04	1000 x 460 mm	260 mm	Ø 60 x 360 mm M12	580 / 1030 mm	400 kg	23 kg
R001/07	2000 x 450 mm	250 mm	Ø 60 x 360 mm M12	590 / 1050 mm	400 kg	37 kg

0642
CUT-OFF MACHINE

For dry cutting of metals, with disc protection guard.

Motor	230 V 50 Hz 2 kW
Disc dimensions	355 x 3.0 x 25.4 mm
Disc speed	3800 rpm
Cut range	± 45°
Cutting capacity	■ 100 x 100 mm - ■ 200 x 40 mm - o 100 mm
Vice opening	155 mm - 190 mm - 230 mm
Net weight	19 kg



0565

FLEXIBLE SHAFT GRINDER

With foot speed variator.



Precision key type chuck	0 - 4 mm
Variable speed	500 ÷ 22000 rpm
Flexible shaft length	900 mm
Motor	230 V 50 Hz 185 W

0568

MULTI CUTTING POWER TOOLS SET

With adjustable stand and flexible shaft grinder.



Precision key type chuck	Ø 3 mm
Variable speed	8000 ÷ 32500 rpm
Flexible shaft length	1000 mm
Stand height	650 mm
Clamp capacity	65 mm
Motor	230 V 50 Hz 135 W

